

CROWN ALLOYS

COMPANY

Section 3 - PHYSICAL and CHEMICAL CHARACTERISTICS

APPEARANCE AND COLOR:

- Dark Orange – No Odor.

SPECIFIC GRAVITY @ 20°C (water = 1): 17.6 mmHg

SOLUBILITY IN WATER: miscible

VAPOR DENSITY (AIR = 1): .82

WATER REACTIVE: water = 1

VAPOR PRESSURE: (PSIG @ 70°F (Aerosols): 120 psig

EVAPORATION RATE (Butyl Acetate = 1): No

BOILING POINT @ 760 mm Hg: N/A

Section 4 - FIRE and EXPLOSION HAZARD DATA

FLAMMABLE LIMITS (in air by volume, %): Lower (LEL): N/A

Upper (UEL): N/A

AUTO IGNITION TEMPERATURE: N/A

FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols): N/A

EXTINGUISHER MEDIA: Non-combustible. Use media compatible with surrounding fire. Water, foam, dry chemical, carbon dioxide can be used.

Brazing flame, welding arc and sparks can ignite combustibles and flammables. Refer to American National Standard Z49.1 "Safety in Welding and Cutting" and "Safe Practices" Code: SP, published by the American Welding Society for fire prevention during the use of welding, brazing and allied procedures.

UNUSUAL FIRE AND EXPLOSION HAZARDS: At high temperatures, overpressurization of containers can result. Cans may burst.

SPECIAL FIRE-FIGHTING PROCEDURES: Wear self-contained respiratory apparatus for protection. Storage containers exposed to fire and/or heat should be kept cool with water.

Section 5 - STABILITY AND REACTIVITY DATA

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Open flames, sparks and/or high temperatures.

HAZARDOUS DECOMPOSITION PRODUCTS: May form carbon monoxide.

MATERIALS WITH WHICH THIS PRODUCT IS INCOMPATIBLE: Acids and strong oxidizing agents.

Hazardous Decomposition Products

Welding/brazing/soldering fumes and gases can not be classified simply. The composition and quantity of both are dependent upon the type of flux, the metal being soldered/brazed/welded and the rods used. Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include; Coatings on the metal being soldered/brazed/welded (such as paint, plating, or galvanizing), the number of welders, the volume of the work area, the quality and the amount of ventilation, the position of the welder's head with respect to the gas plume, the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing activities), the process and procedures, as well as the soldering/brazing/welding consumables.

When this anti-spatter is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 2. Decomposition products of normal operation include those originating from the volatilization, reaction, or oxidation of the materials shown in Section 2, plus those from the base metal, coatings, etc., as noted above. Gaseous reaction products may include carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from an arc, in addition to the shielding gases like argon and helium, whenever they are employed.

One recommended way to determine the composition and quantity of fumes and gases to which workers are exposed is to take an air sample inside the welder's helmet if worn or in the worker's breathing zone. See ANSI/AWS F1.1 "Method for Sampling Airborne Particles Generated by Welding and Allied Processes" and "Characterization of Arc Welding Fume" available from the American Welding Society, 550 N.W. LeJeune Road, Miami, FL 33126.

CROWN ALLOYS **COMPANY**

Section 6 - HEALTH HAZARD DATA

- **EYES:** Contact with this anti-spatter will cause slight irritation to the eyes.
- **SKIN:** Contact with this anti-spatter may cause slight irritation to the skin.
- **INGESTION:** Ingesting this anti-spatter may cause slight nausea.
- **INHALATION:** During welding/brazing/soldering operations the fumes generated may cause headaches, dizziness and/or nausea.

Section 7 - PRECAUTIONS FOR SAFE HANDLING & USE/APPLICABLE CONTROL MEASURES

VENTILATION AND ENGINEERING CONTROLS: Maintain exposures below the acceptable exposure levels (see Section 2). Use industrial hygiene air monitoring to ensure that your use of this product does not create exposures that exceed the recommended exposure limits. Always use exhaust ventilation in user operations such as high temperature cutting, grinding, welding, brazing and soldering. Train the welder to keep his head out of the fume plume. Maintain air flow away from the user to remove all fumes and dusts, so that the PEL is never exceeded. Adhere to Environmental regulations for exhausts. Confined spaces require adequate ventilation and/or air supplied respirators. Read and understand the manufacturer's instructions and the precautionary label on the product. See American National Standard Z49.1, *Safety in Welding, Cutting, and Allied Processes*, published by the American Welding Society, 550 N.W. LeJeune Road, Miami, FL 33126 and OSHA Publication 2206 (29CFR1910), US Government Printing Office, Washington, D.C. 20402 for more details on many of the following.

RESPIRATORY PROTECTION: Use respirable fume respirator or air supplied respirator when welding in confined space or where local exhaust or ventilation does not keep exposure below PEL's (see Section 2). Use only NIOSH approved respirators in accordance with 29 CFR 1910.134 – Respiratory Protection. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (1910.134-1998).

FOR MAXIMUM SAFETY, BE CERTIFIED FOR AND WEAR A RESPIRATOR AT ALL TIMES WHEN WELDING OR BRAZING OR SOLDERING!

EYE PROTECTION: Ensure eyewash/safety shower stations are available near areas where these products are used. Wear safety glasses, goggles or face-shield with filter lens of appropriate shade number (per ANSI Z49.1-1988, "Safety in Welding and Cutting"). Goggles must be chemically tight safety goggles. Do NOT wear contact lenses.

PROTECTIVE CLOTHING: Protective gloves are recommended that are chemical and acid impervious. Since welding/brazing/soldering involves high temperatures, be sure the gloves are designed for high temperature applications to prevent burns.

WORK PRACTICES AND HYGIENE PRACTICES: As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash hands after handling this product. Do not eat or drink while handling this product. Do not smoke or apply cosmetics in areas where exposures exist.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain the spill and then absorb, sweep-up and dispose of material. Flush the area to a chemical sewer.

WASTE DISPOSAL METHOD: Prevent waste from contaminating surrounding environment. Discard any product, residue, disposable container or liner in an environmentally acceptable manner, in full compliance with federal, state and local regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store this product at ambient conditions. Do not store at temperatures above 130°F. Keep under extremely dry and controlled conditions. Wash thoroughly after handling to remove all residue. KEEP OUT OF REACH OF CHILDREN! Professionally wash contaminated clothing before re-use.

CROWN ALLOYS

COMPANY

Section 8 - FIRST AID MEASURES

- **EYE EXPOSURE:** Flush eyes with plenty of water or saline for at least 15 minutes to remove all residue. Consult a physician.
- **SKIN EXPOSURE:** Wash thoroughly with soap and water. If irritation should occur, contact a physician.
- **INHALATION EXPOSURE:** Remove to fresh air. Resuscitate if necessary. Call a physician; advise of chemical composition (Section 2) and potential health hazards (Section 6).
- **INGESTION EXPOSURE:** Drink large volumes of water. Call a physician. Advise of chemical composition (Section 2) and potential health effects (Section 6).
- **RECOMMENDATIONS TO PHYSICIANS:** Treat symptoms and eliminate overexposure.

Section 9 – REGULATORY INFORMATION

TOXIC SUBSTANCE CONTROL ACT:

All components of this product are listed within the TSCA inventory

HMIS Rating:	Health Hazard	1
	Flammability	0
	Reactivity	0
	Personal Protection	B
NFPA Rating:	Health Hazard	0
	Flammability	0
	Reactivity	0
	Special	None

HAZARD RATING
4 – Severe Hazard
3 – Serious Hazard
2 – Moderate Hazard
1 – Slight Hazard
0 – Minimal Hazard

Section 10 – OPTIONAL INFORMATION

DEPARTMENT OF TRANSPORTATION: (Domestic Ground)

DOT Hazard Classification: Consumer Commodity ORMD 48580 sub 3

STATE RIGHT-TO-KNOW PROGRAMS:

Pennsylvania: All materials of Section 2 are listed in PA code Title 34.

California: As currently manufactured, this material contains no compounds subject to the reporting and labeling requirements of Proposition 65.

Section 11 – DEFINITIONS OF TERMS

CAS No. - Chemical Abstracts Service Number **PEL** - Permissible Exposure Level **TLV** - Threshold Limit Value
TWA - Time Weighted Average **STEL** - Short Term Exposure Limit **IARC** – International Agency for Research on Cancer
NIOSH – National Institute of Occupational Safety and Health **OSHA** – U.S. Occupational Safety and Health Administration
TDLo – the lowest dose to cause a symptom **TCLo** – the lowest concentration to cause a symptom
TDo, LDLo, and LDo, or TC, TCo, LCLo, and LCo – the lowest dose (or concentration) to cause lethal or toxic effects.
SARA – Superfund Amendments and Reauthorization Act **ACGIH** – American Conference of Governmental Industrial Hygienists
LD₅₀ & LC₅₀ – These values are the amount of a substance given to the stated species that causes 50% of that species to die.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES: The information in this document is believed to be correct as of the date issued. However, this information is provided without any representation or warranty, expressed or implied, regarding accuracy or correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons we do not assume responsibility and expressly disclaim liability of loss, damage, or expense arising from it or any way connected with the handling, storage, use, or disposal of this product. Data may be changed from time to time. Be sure to consult the latest edition of the MSDS.