



!!!! WARNING !!!!



WELDING FUMES AND GASES CAN BE DANGEROUS TO YOUR HEALTH.

BEFORE USING THIS PRODUCT THE WELDER (END-USER) MUST READ AND UNDERSTAND THE COMPLETE PRODUCT WARNING LABEL AND MATERIAL SAFETY DATA SHEET (MSDS).

THE MATERIAL SAFETY DATA SHEET (MSDS) WHICH OUTLINES THE POTENTIAL HEALTH HAZARDS AND SAFETY INFORMATION RELATED TO THIS PRODUCT CAN BE DOWNLOADED FROM THE MSDS PORTION OF THIS WEBSITE. IT IS ALSO AVAILABLE FROM YOUR EMPLOYER AND WELDING SUPPLY DISTRIBUTOR.

DO NOT PROCEED WITH USE OF THIS PRODUCT UNTIL YOU READ AND UNDERSTAND THE MATERIAL SAFETY DATA SHEET (MSDS) AND PRODUCT WARNING STATEMENT.

BE SURE TO CONSULT THE LATEST VERSION OF THE MSDS.

SEE THE PRODUCT WARNING LABEL AND MSDS FOR COMPLETE WARNING INFORMATION.



CROWN ALLOYS

COMPANY

30105 STEPHENSON HWY.
MADISON HEIGHTS, MI. 48071
(248) 588-3790 • (800) 521-7878

Crown 69-W

Water Based Anti-Spatter

Typical Applications:

The **Crown 69-W** can be used on MIG nozzles, cups, contact tips, jigs and fixtures, or parts to be welded where spatter is objectionable.

Specifications:

The **Crown 69-W** is a BIODEGRADABLE, NON-TOXIC, NON-FLAMMABLE, WATER-BASED Anti-Spatter. The 16 oz. aerosol can is inert gas propelled. If the **Crown 69-W** is not wiped off after welding it could cause rusting on carbon steels.

Procedure:

Point arrow on nozzle toward object to be protected and spray freely. On flat surfaces, spray with sweeping motion about 10" from surface. For nozzles and tips use rotating motion being sure to cover inside and outside of entire tip. Bulk material may be painted on, used as a dip, or used in hand sprayer. After welding wipe off spatter and excess of **Crown 69-W** with cloth.

Packaging:

16 oz aerosol can
1 gallon can
5 gallon pail
55 gallon drum